



62 Oil Stain (White Spirit)

PRODUCT DATA

Description

Light fast oil stain for bare or unfinished interior wood including doors, floors, woodwork, furniture and cabinets. Can be over-coated with varnish or lacquer.

Area of use

Interior

Substrates

Wood

Packing

5 litres (min batch 200L)

Physical Constants

Colour:	Light and Medium
Finish:	Matt
Volume solids:	N/A
Theoretical spreading rate:	15 – 20 sq.metres per litre
Flash point:	38°C
Specific gravity:	0.83
Dry to touch:	2 – 3 hours
Overcoating time:	6 – 8 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method:	Brush or cloth
Thinner:	N/A
Cleaning of tools:	White Spirit or Turps Sub

Surface condition The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.