



Blackboard Paint

PRODUCT DATA

Description

A tough matt black paint for blackboards and general surfaces. A single-pack solvent based easy to use paint. Excellent opacity.

Area of use

Interior and exterior

Substrates

Wood, metal and some composite materials

Packing

1 Litre, 2.5 Litres and 5 Litres

Physical Constants

Colour:	Black
Finish:	Matt
Volume solids:	52%
Theoretical spreading rate:	15 sq. metres per litre
Flash point:	38°C
Specific gravity:	1.3 kg/litre
Dry to touch:	4 hours (20°C)
Overcoating time:	16 hours

The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. **The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method:	Brush, roller, Conventional spray or airless spray
Thinner:	White spirit
Cleaning of tools:	White spirit

<u>Surface condition</u>	The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.
---------------------------------	--

Please refer to the Material Safety Data Sheet for further information.

For additional guidance please contact your local Technical Sales Representative.

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.