



One Coat High Build Gloss

PRODUCT DATA

Description

A high quality one coat alkyd resin system suitable for kitchens, bathrooms, doors, window frames, furniture and woodwork in general. Also ideal for metal surfaces. Designed for top-class work where the highest standards of finish, durability and colour retention are required.

Area of use

Interior and exterior.

Substrates

Metal surfaces, woodwork, fibreboards etc.

Packing

1 litre and 2.5 litres (min batch 200L)

Physical Constants

Colours: White (Special Colours on request)

Finish: High gloss

Volume solids: 45%

Theoretical spreading rate: 15 sq. metres per litre

Flash point: 38°C

Specific gravity: 1.20

Dry to touch: 6 hours (20°C)

Overcoating time: 16 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method: Brush, roller, conventional and airless spray

Thinner: White Spirit

Cleaning of tools: White Spirit

Surface condition

The surface should be stable, firm, dry and free of dust, dirt, rust grease and oil. Remove any loose old paint. It is recommended to apply a primer prior to any filling procedure. Touch-up with primer on areas repaired with filler. Prime all bare areas with a suitable primer. Undercoat may be required.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

Please check colour before use. If using multiple cans please check batch numbers are the same.

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.