



Asipo Barrier

PRODUCT DATA

Description

Designed to form a barrier within the plaster or rendered surface on walls or ceilings to prevent Mould spores re-appearing.

Area of use

Internal and External

Substrates

Brick, plaster and rendered surfaces

Packing

5 litres

Physical Constants

Colour: Clear

Finish: N/A

Volume solids: N/A

Theoretical spreading rate: 8 - 10 sq. metres per diluted litre

Flash point: N/A

Specific gravity: 1.0 – 1.01

Dry to touch: 30 minutes

Over-coating time: 1 hour

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method: Brush, sponge or cloth

Thinner: N/A

Cleaning of tools: Water

Surface condition

The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.