



Asiposeal

PRODUCT DATA

Description

Non-silicone based, single pack solvent-borne protective coating. Clear coating used to seal external masonry areas. Proven effective to stop water penetration. Provides long-term protection against surface contamination by air-borne spores.

Area of use

Exterior

Substrates

Concrete, render, brick and general masonry

Packing

5 litres (min batch 100L)

Physical Constants

Colour:	Clear
Finish:	Semi Gloss
Volume solids:	12%
Theoretical spreading rate:	10 - 20 sq. metres per litre (dependant on porosity)
Flash point:	38°C
Specific gravity:	0.85
Dry to touch:	2 hours (20°C)
Overcoating time:	6 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method:	Brush or spray
Thinner:	White Spirit
Cleaning of tools:	White Spirit

Surface condition The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

Please check colour before use. If using multiple cans please check batch numbers are the same.

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.