

# FLAG Multi-Purpose Metallic Primer



## PRODUCT DATA

---

### **Description:**

Universal primer suitable for above and below the waterline on all substrates with good waterproofing and corrosion resisting performance. Also suitable as a primer or barrier coat under FLAG and other traditional antifoulings. Contains leafing pigment (excellent sealing/binding properties). Easy to apply and relatively quick drying.

### **Area of use:**

Boat hulls, topsides and superstructure.

### **Substrates:**

GRP, wood, steel and ferro cement.

### **Packing:**

1 litre and 2.5 litre

### **Physical Constants:**

|                             |                       |
|-----------------------------|-----------------------|
| Colour:                     | Grey                  |
| Finish:                     | Matt                  |
| Volume solids:              | 60%                   |
| Theoretical spreading rate: | 12sq.metres per litre |
| Flash point:                | 42°C                  |
| Specific gravity:           | 1.17                  |
| Dry to touch:               | 2 hours               |
| Overcoating time:           | 6 hours               |

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

### **Application Details:**

|                     |   |
|---------------------|---|
| Application method: | Brush Conventional spray Airless spray Roller |
| Thinner:            | FLAG Antifouling Thinners                     |
| Cleaning of tools:  | FLAG Antifouling Thinners                     |

### **Surface condition:**

The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease, oil and salt.

*Please refer to the Material Safety Data Sheet for further information.  
For additional guidance please contact your local Technical Sales Representative.*