



Flag Tile Paint (CLEAR)

PRODUCT DATA

Description:

A protective clear top-coat for use over Flag Tile Paint. Designed to provide additional durability for the protection of commercial areas.

Substrates:

Ceramic Tiles

Physical Constants:

Colours:	Clear
Finish:	Gloss
Volume solids:	46%
Theoretical spreading rate:	20 sq. metres per litre
Flash point:	38°C
Specific gravity:	0.93
Dry to touch:	2 hours (20°C)
Overcoating time:	4-8 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method:	Brush/Roller <i>Recommended rollers are short pile sheepskin or synthetic fibre Foam rollers are not recommended</i>
Thinner:	White Spirit
Cleaning of tools:	White Spirit

Surface condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

Please refer to the Material Safety Data Sheet for further information.

For additional guidance please contact your local Technical Sales Representative.

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.