



MDF Primer

## PRODUCT DATA

---

### **Description:**

A water thinned primer with excellent adhesion and opacity, for use on MDF. Specially recommended for situations where speed of application, economy or low odour during the drying process is important.

### **Area of use:**

Interior and exterior

### **Substrates:**

MDF

### **Packing:**

1 Litre and 2.5 Litres

### **Physical Constants:**

Colour:	White
Finish:	Matt
Volume solids:	48%
Theoretical spreading rate:	12 sq. metres per litre
Flash point:	N/A
Specific gravity:	1.25
Dry to touch:	2 hours (20°C)
Over-coating time:	4 - 8 hours

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

### **Application Details:**

Application method:	Brush / Roller / Conventional Spray / Airless Spray
Thinner:	Water
Cleaning of tools:	Water

### **Surface Condition:**

The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil. It is recommended to apply a primer prior to the specified filling procedure. Touch-up with primer on areas repaired with filler is recommended prior to application of topcoats.

*Please refer to the Material Safety Data Sheet for further information.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.