



Patent Knotting

PRODUCT DATA

Description

Traditional shellac based sealer for resinous knots on timber. Ideal for restoration purposes. Provides ongoing protection against the resin of knots. Formulated to seal knots and prevent resin seepage. Very popular for use on pine.

Area of use

Interior and exterior

Substrates

Wood

Packing

500ml or 5 litres

Physical Constants

Colour:	Dark Amber
Finish:	Gloss
Volume solids:	33%
Theoretical spreading rate:	16 sq.meters per litre
Flash point:	18°C
Specific gravity:	0.88
Dry to touch:	15 – 20 minutes
Overcoating time:	30 minutes

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method:	Brush or Cloth
Thinner:	Methylated Spirit
Cleaning of tools:	Methylated Spirit

Surface condition The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.

Flag Paints Ltd. 8 Springfield Road, Burnham on Crouch, CM0 8UA, Tel:+44 1621 785173, Fax:+44 1621 785393