



T10009 Thinners (Xylene)

PRODUCT DATA

Description

Thinner for use with quick air-drying paint finishes. Can be used as a degreaser on metal surfaces.

Area of use

Interior and exterior

Substrates

N/A

Packing

1 litre and 5 litres (1 litre min batch 100L)

Physical Constants:

Colour:	Clear
Finish:	N/A
Volume solids:	N/A
Theoretical spreading rate:	N/A
Flash point:	23°C
Specific gravity:	0.85
Dry to touch:	N/A
Overcoating time:	N/A

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method:	N/A
Thinner:	N/A
Cleaning of tools:	N/A

Surface condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.